REVISIONS

– HARDIPLANK LAP SIDING SELECT CEDAR MILL 5/16" THK. 8" EXPOSURE TYPICAL OVER - ARCHTECTURAL STYLE SHINGLES COORDINATE COLOR AND MATERIAL

WITH OWNER. SHINGLES OVER 30# FELT. FASTEN PER MFG. FLASH AT BASE, CAPS, AND VALLEYS GALV. GUTTER ON 2x8 FASCIA W/DOWNSPOUTS. SEE OWNER FOR COLOR & FINISH.

- FOR OUTLOOKER SEE 5/A7.0 TYPICAL

— CLIPPED GABLE

15# FELT

- 4" HARDITRIM AT WINDOWS, DOORS, INSIDE CORNERS, AND OUTSIDE CORNERS TYPICAL APPLY PER MFG.

HARDIPLANK LAP SIDING SELECT CEDAR MILL 5/16" THK. 8" EXPOSURE TYPICAL OVER 15# FELT. APPLY FELT HORIZONTALLY, WITH UPPER LAYER LAPPED OVER LOWER LAYER NOT LESS THAN 2". WHERE JOINS OCCUR, FELT SHALL BE LAPPED NOT LESS THAN 6". CAULK ENDS, COVERED WITH A BATTEN OR SEALED AND INSTALLED OVER A

STRIP OF FLASHING. USE 6d CORROSION RESISTANT NAILS. FACE NAILING: (2) NAILS AT EACH STUD CONCEALED NAILING: (1) 6D GALV. BOX NAIL AT EACH STUD.

DATE JUN 6, 05 SCALE AS SHOWN

OREGON HOME DESIGN DESIGN, DRAFTING, & ENGINEERING

MAM E BARD

EXPIRES: 12/31/05

WILLIAM E. BARLOW, P.E. O. BOX 2023, CORVALLIS, OR 97339 TEL.: (541)929-8111

SHEET

SCALE: 1/4" = 1'-0"

MINDOMS TYPICAL—

- - HOUSE NUMBER